



Flexible in:

- wall cutting
- door and window opening
- trimming of great cutting length

HAND-SAW HE160

An allrounder for repair works throughout the construction industry

Ideal to cut concrete, masonry or natural stone.

The shape of this hand saw and the position of blade-guard make this product extremely flexible and allow good visibility on the cutting area. The water injection system effectively remove cutting dust.

Power, agility and flexibility are the main qualities of the HE160. An accessory for this product allow to flush-cut.

The maximum admissible blade diameter of \varnothing 400 mm can be used optimally by a strong 3kW electric motor.

Technical Data

HE160

Electric motor:	230 V, 14 A
Power:	3,0 kW
Electronic speed regulation:	2500 min ⁻¹
Load speed:	1700 min ⁻¹
Max. cutting depth \varnothing 400 mm:	158 mm
Cutting depth:	adjustable
Arbor hole:	25,4 mm
Softstart electronic:	yes
Electric safety clutch:	yes
Weight:	11 kg

GÖLZ HE160

HE160 standard version, 230 V, 3 kW	0295 150 1087	1.290,-
HE160F flush cutting version, 230 V, 3 kW	0295 150 1088	1.320,-

Accessories

flush cut blade guard with flush cut flange	0295 150 1090	115,-
Transport case	0295 150 1091	50,-
Cutting depth control	BD505101	62,-